



CarMover



WWW.TRACKEDMACHINES.COM



CARMOVER: THE SOLUTION FOR VEHICLE HANDLING

CarMover is the ideal tool for moving vehicles on flat surfaces such as asphalt parking lots, warehouses, and showrooms with concrete or resin floors.

Thanks to innovative technical solutions, this unique device allows you to move immobilized vehicles without towing them, by lifting them instead. With its electric motor, the EasyMover 4W is perfect for working in tight spaces and simplifies operations without requiring any effort from the operator.

Why choosing CarMover:

- It allows vehicles to be parked very close to each other, optimizing space usage.
- It can overcome small obstacles.
- It emits no exhaust gases, making it suitable for use in body shops or warehouses.
- Ease of use.



STRENGTHS



Exceptional performance: maximum speed of 8.5 km/h and lifting capacity of cars up to 4000 kg.



Ergonomic: reclining cushioned platform with stable, adjustable side rails.



Maneuverability: hydraulically dampened support wheels for better traction.



OPERATING PRINCIPLE OF THE CARMOVER 2W

The operating principle of the CarMover 2W is to slide the cart under the vehicle and lock the wheels using a hydraulic mechanism. In addition to locking the wheels, this mechanism also lifts them a few centimeters off the ground, completely freeing them from contact with the surface. The vehicle is then ready to be moved.

OPERATING PRINCIPLE OF THE CARMOVER 4W

The operating principle of the CarMover 4W is to slide the cart under the vehicle and lock the wheels using a hydraulic mechanism. Once the first set of wheels is locked, the cart is moved until it is positioned near the remaining free axle, where a locking mechanism similar to the previous one secures the last two wheels. When the vehicle is fully immobilized, the lift command is activated, allowing the entire vehicle to be raised a few centimeters, completely freeing the wheels from contact with the ground.

The CarMover 4W can move vehicles with all wheels locked and, thanks to its hydraulic telescopic system, it adapts perfectly to all vehicle sizes, from compact city cars to large electric SUVs.



OUR CARMOVER LINE

CarMover 2W Lite / 2W Lite E



CarMover 2W Pro



CarMover 4W Pro



OPERATING PRINCIPLE OF THE CARMOVER 2W

The operating principle of the CarMover 2W is to slide the cart under the vehicle and lock the wheels using a hydraulic mechanism. In addition to locking the wheels, this mechanism also lifts them a few centimeters off the ground, completely freeing them from contact with the surface. The vehicle is then ready to be moved.

OPERATING PRINCIPLE OF THE CARMOVER 4W

The operating principle of the CarMover 4W is to slide the cart under the vehicle and lock the wheels using a hydraulic mechanism. Once the first set of wheels is locked, the cart is moved until it is positioned near the remaining free axle, where a locking mechanism similar to the previous one secures the last two wheels. When the vehicle is fully immobilized, the lift command is activated, allowing the entire vehicle to be raised a few centimeters, completely freeing the wheels from contact with the ground.

The CarMover 4W can move vehicles with all wheels locked and, thanks to its hydraulic telescopic system, it adapts perfectly to all vehicle sizes, from compact city cars to large electric SUVs.



2W LITE E



CARMOVER 2W LITE E

Traction unit	STILL
Platform type	/
Maneuver	GROUND OPERATION
Power	ELECTRIC
Battery	2PzS
Battery capacity	150 Ah
Brake	ELECTROMAGNETIC
Hydraulic power	/

FEATURES

Car lifting up to max	4000 kg
Operating time	4 h
Charging time	6 h
Max speed	6 km/h
Lift Platform	FIXED

VEHICLE DIMENSIONS

Max width	1850 mm
Min width	1080 mm
Front length	1200 mm

2W LITE



CARMOVER 2W LITE

Traction unit	STILL
Platform type	/
Maneuver	GROUND OPERATION
Power	ELECTRIC
Battery	2PzS
Battery capacity	150 Ah
Brake	ELECTROMAGNETIC
Hydraulic power	0.7 kW

FEATURES

Car lifting up to max	4000 kg
Operating time	4 h
Charging time	6 h
Max speed	6 km/h
Lift Platform	EXTENSIBLE

VEHICLE DIMENSIONS

Max width	1850 mm
Min width	1080 mm
Front length	1200 mm

2W PRO



CARMOVER 2W PRO

Traction unit
Platform type
Maneuver
Power
Battery
Battery capacity
Brake
Hydraulic power

GROUND OPERATION / ON BOARD

STILL
RECLINING
ELECTRIC
2PzS
250 Ah
ELECTROMAGNETIC
0.9 kW

FEATURES

Car lifting up to max
Operating time
Charging time
Max speed
Lift Platform

4000 kg
6 h
8 h
8,5 km/h
EXTENSIBLE

VEHICLE DIMENSIONS

Max width
Min width
Front length

1850 mm
1080 mm
1200 mm

4W PRO



CARMOVER 4W PRO

Traction unit
Platform type
Maneuver
Power
Battery
Battery capacity
Brake
Hydraulic power

GROUND OPERATION / ON BOARD

STILL
RECLINING
ELECTRIC
2PzS
250 Ah
ELECTROMAGNETIC
0.9 kW

FEATURES

Car lifting up to max
Operating time
Charging time
Max speed
Lift Platform

3000 kg
6 h
8 h
8.5 km/h
EXTENSIBLE

VEHICLE DIMENSIONS

Max width
Min width
Front length

1850 mm
1080 mm
1145 mm







TRACKED MACHINES ITALIA S.R.L.

Via A. Volta, 24 - 37026 Settimo di Pescantina (VR)

info@trackedmachines.com | +39 379 273 4824

www.trackedmachines.com